

# AdaSockets reference manual

---

for AdaSockets version 1.11.1  
7 October 2017

Samuel Tardieu

---

Copyright © 2002-2017 Samuel Tardieu

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided also that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions.

# Table of Contents

<b>1</b>	<b>What is AdaSockets?</b>	<b>1</b>
<b>2</b>	<b>Installing AdaSockets</b>	<b>3</b>
<b>3</b>	<b>Using AdaSockets</b>	<b>5</b>
3.1	Compiling an Ada application	5
3.2	Setting up unicast sockets	5
3.3	Setting up multicast sockets	5
3.4	Sending and receiving data	6
3.4.1	Raw data manipulation	6
3.4.2	String-oriented exchanges	6
<b>4</b>	<b>Sockets package</b>	<b>7</b>
	Accept_Socket (procedure)	7
	Bind (procedure)	8
	Connect (procedure)	8
	Get (function)	9
	Get_Char (function)	9
	Get_Line (function)	10
	Get_Line (procedure)	10
	Get_Receive_Queue_Size (function)	11
	Get_Send_Queue_Size (function)	11
	Getsockopt (procedure)	12
	Listen (procedure)	12
	New_Line (procedure)	13
	Put (procedure)	13
	Put_Line (procedure)	14
	Receive (function)	14
	Receive (procedure)	15
	Receive_Some (procedure)	15
	Send (procedure)	16
	Set_Buffer (procedure)	16
	Setsockopt (procedure)	16
	Shutdown (procedure)	17
	Socket (procedure)	17
	Unset_Buffer (procedure)	18
<b>5</b>	<b>Sockets.Multicast package</b>	<b>19</b>
	Create_Multicast_Socket (function)	19
	Create_Multicast_Socket (function)	20

<b>6</b>	<b>Sockets.Naming package</b>	<b>21</b>
	Address_Of (function)	21
	Any_Address (function)	22
	Get_Peer_Addr (function)	22
	Get_Peer_Port (function)	22
	Get_Sock_Addr (function)	22
	Get_Sock_Port (function)	23
	Host_Name (function)	23
	Image (function)	23
	Info_Of_Name_Or_IP (function)	24
	Is_IP_Address (function)	24
	Name_Of (function)	24
	Value (function)	25
	<b>Appendix A Contributors</b>	<b>27</b>
	<b>Appendix B Resources on the Internet</b>	<b>29</b>
	<b>Index</b>	<b>31</b>

# 1 What is AdaSockets?

AdaSockets is a set of free software Ada packages allowing Ada programmers to use the so-called BSD sockets from their favourite programming language. AdaSockets has been designed and tested with the GNAT free software Ada compiler, but should be portable to other compilers quite easily.

Starting from release 3.14, the GNAT compiler started to integrate a `GNAT.Sockets` package. However, this package is GNAT specific and contains at this time less features than AdaSockets. At some point, AdaSockets may use `GNAT.Sockets` as its underlying sockets structure.

AdaSockets philosophy is to help the Ada programmer by providing easy-to-use objects. Special care has been taken to ensure that performances do however remain good.



## 2 Installing AdaSockets

Installing AdaSockets on a Unix or OpenVMS machine is as simple as typing a few commands. Once you got the latest version of AdaSockets (see Appendix B [Resources on the Internet], page 29), uncompress and untar it and go to the top-level directory of the distribution.

You must configure the AdaSockets distribution by using the **configure** command, such as in:

```
./configure --prefix=/users/sam/adasockets
```

If you want to install AdaSockets under the **/usr/local** hierarchy, you do not need to specify the **--prefix** option. Make sure you have write permission on the target directories.

Once AdaSockets is configured, you can compile and install it by using the **make** command:

```
make install
```

The GNU make program is recommended but not mandatory. On your system, it may be installed under the **gmake** name.





## 3 Using AdaSockets

### 3.1 Compiling an Ada application

AdaSockets comes with an `adasockets-config` application that can be used to retrieve installation parameters while using `gnatmake` to compile your Ada application. The `--cflags` parameters tells `adasockets-config` to output the path to the Ada packages sources, while `--libs` asks for the path to the Ada library.

```
gnatmake 'adasockets-config --cflags' mainprog
        -larg 'adasockets-config --libs'
```

### 3.2 Setting up unicast sockets

Unicast sockets are used everywhere on the Internet, for surfing the web, sending electronic mails or accessing remote files. They come in two flavours:

- |     |  |
|-----|--|
| TCP | TCP is a connected mode, in which packets are sent in a reliable and ordered way. Everything sent at one end will eventually arrive in the same order at the other end, the underlying operating system takes care of retransmitting missing packets and reordering out-of-order ones.   |
| UDP | UDP is a non-connected mode. A packet sent on a UDP socket may or may not arrive at the other end. This is a much lighter protocol when reliability is not needed as the operating system does not have to use large buffers to reorder packets. Also, this generates less traffic as no acknowledgments need to be sent by the kernels. |

The package `Sockets` defines a `Socket_FD` tagged type. An instance of this type (or of any of its descendants) represents an incoming or outgoing socket. Two different kinds of sockets can be created: unicast (one-to-one) and multicast (many-to-many).

### 3.3 Setting up multicast sockets

Multicast sockets are used for group communication over the Internet. To use multicast sockets, you must be connected to a multicast network and use a multicast-enabled operating system (such as most Unices, Linux or even recent Windows versions). Unless you are connected to the mbone (multicast backbone) or have setup a private multicast network, you will only be able to use multicast on your local network.

A multicast socket is somewhat similar to a UDP socket; in particular, packets may be lost or misordered.

You can create a multicast socket using the function `Create_Multicast_Socket` in the package `Sockets.Multicast`. This function returns a `Multicast_Socket_FD` object, which derives from `Socket_FD`.

`Create_Multicast_Socket` takes care of the whole setup of your multicast socket. You do not need to call any additionnal subprogram before using it. In particular, `Create_Multicast_Socket` will take care of registering the multicast socket to the operating system, so that the latter can tell the connected routers to propagate the subscription to the mbone as needed.

## 3.4 Sending and receiving data

In AdaSockets, data can be sent and received in three different ways: raw, string-oriented and stream-oriented.

### 3.4.1 Raw data manipulation

Raw data is manipulated using the predefined `Ada.Streams.Stream_Element_Array` Ada type. This corresponds to an array of bytes, or an `unsigned char *` in the C programming language.

### 3.4.2 String-oriented exchanges

String-oriented exchanges provides the programmer with `Ada.Text_IO` like subprograms. Most Internet protocols are line-oriented and those subprograms are perfectly suited to implement those.

When sending data, the classical `CR + LF` sequence will be sent at the end of each line. When receiving data, `CR` characters are discarded and `LF` is used as the end-of-line marker.

The `Get` function is tied to the size of the operating system buffer. It is better to use `Get_Line` to get a full line. The line can be as long as the length of the Ada buffer. The Ada buffer can be adjusted by using the `Set_Buffer` and `Unset_Buffer` procedures.

When using string-oriented exchanges with datagram protocols such as UDP, setting a buffer using `Set_Buffer` for the receiving socket is mandatory. If you don't, the receiving socket will loose data and will be unable to reconstitute the string.



SEE ALSO [Bind (procedure)], page 8,  
 [Listen (procedure)], page 12,  
 [Shutdown (procedure)], page 17,  
 [Socket (procedure)], page 17.

## Bind (procedure)

PURPOSE Associate a local port to a socket

PROTOTYPE

```
procedure Bind (Socket : Socket_FD;                      [Sockets.Bind]
               Port : Natural; Host : String := "");
```

PARAMETERS

<i>Socket</i>	in	Initialized socket object
<i>Port</i>	in	Local port to bind to
<i>Host</i>	in	Local interface to bind to

DESCRIPTION

This procedure requests a local port from the operating system. If 0 is given in *Port*, the system will assign a free port whose number can later be retrieved using [Get\_Sock\_Port (function)], page 23. Also, most operating systems require special privileges if you want to bind to ports below 1024.

If *Host* is not the empty string, it must contain the IP address of a local interface to bind to, or a name which resolves into such an address. If an empty string is given (the default), the socket will be bound to all the available interfaces.

EXCEPTIONS

<b>Socket_Error</b>	Requested port or interface not available
---------------------	---

SEE ALSO [Listen (procedure)], page 12,  
 [Socket (procedure)], page 17.

## Connect (procedure)

PURPOSE Connect a socket on a given host/port

PROTOTYPE

```
procedure Connect (Socket : Socket_FD;                  [Sockets.Connect]
                  Host : String; Port : Positive);
```

PARAMETERS

<i>Socket</i>	in	Initialized socket object
<i>Host</i>	in	Host to connect to
<i>Port</i>	in	Port to connect to

DESCRIPTION

This procedure connects an initialized socket to a given host on a given port. In the case of a TCP socket, a real connection is attempted. In the case of a UDP socket, no connection takes place but the endpoint coordinates are recorded.

EXCEPTIONS

<b>Connection_Refused</b>	The connection has been refused by the server
<b>Socket_Error</b>	Another error occurred during the connection

## EXAMPLE

```

declare
    Sock : Socket_FD;
begin
    -- Create a TCP socket
    Socket (Sock, PF_INET, SOCK_STREAM);
    -- Connect it to rfc1149.net's mail server
    Connect (Sock, "mail.rfc1149.net", 25);
    -- Do a mail transaction then close the socket
    [...]
end;
```

SEE ALSO [Socket (procedure)], page 17.

**Get (function)**

PURPOSE Get a string from a remote host

## PROTOTYPE

```

function Get (Socket : Socket_FD'Class)           [Sockets.Get]
    return String;
```

## PARAMETERS

*Socket*                      in                      Initialized and connected socket object

## RETURN VALUE

Some characters that have been received

## DESCRIPTION

This function receives some characters from a remote host. As soon that at least one character is available, the current reception buffer is returned.

There is usually little gain in using this function whose behaviour is comparable to the one of [Receive (function)], page 14. Other functions such as [Get\_Char (function)], page 9, or [Get\_Line (function)], page 10, allow more structured programming.

However, this function may be used to avoid losing characters when calling [Unset\_Buffer (procedure)], page 18, if, for some reason, the remote host may have sent some.

## EXCEPTIONS

*Connection\_Closed*                      Peer has closed the connection before sending any data

**Get\_Char (function)**

PURPOSE Get a character from a remote host

## PROTOTYPE

```

function Get_Char (Socket : Socket_FD'Class)      [Sockets.Get_Char]
    return Character;
```

## PARAMETERS

*Socket*                      in                      Initialized and connected socket object

**RETURN VALUE**

One character sent by the remote host

**DESCRIPTION**

This function receives exactly one character from the remote host.

**EXCEPTIONS**

**Connection\_Closed**                      Peer has closed the connection before sending the character

**SEE ALSO**    [Get (function)], page 9,  
               [Get\_Line (function)], page 10,  
               [Get\_Line (procedure)], page 10,  
               [Receive (procedure)], page 15,  
               [Set\_Buffer (procedure)], page 16.

**Get\_Line (function)**

**PURPOSE**    Get a whole line from a remote host

**PROTOTYPE**

```
function Get_Line (Socket : Socket_FD'Class;      [Sockets.Get_Line]
                  Max_Length : Positive := 2048)
                  return String;
```

**PARAMETERS**

<i>Socket</i>	in	Initialized and connected socket object
<i>Max_Length</i>	in	Maximum returned line length

**RETURN VALUE**

A line without the CR and LF separators

**DESCRIPTION**

This function receives one line from the remote host. A line consists into zero or more characters followed by an optional CR and by a LF. Those terminators are stripped before the line is returned.

This function blocks until one full line has been received. The line length is limited with the value of the Max\_Length argument, to avoid exhaustion of the secondary stack.

**EXCEPTIONS**

**Connection\_Closed**                      Peer has closed the connection before sending a whole line

**SEE ALSO**    [Get (function)], page 9,  
               [Get\_Char (function)], page 9,  
               [Get\_Line (procedure)], page 10,  
               [Receive (procedure)], page 15,  
               [Set\_Buffer (procedure)], page 16.

**Get\_Line (procedure)**

**PURPOSE**    Get a whole line from a remote host

## PROTOTYPE

```

procedure Get_Line (Socket : Socket_FD'Class;      [Sockets.Get_Line]
                    Str : in out String; Last : out Natural);

```

## PARAMETERS

<i>Socket</i>	<i>in</i>	Initialized and connected socket object
<i>Str</i>	<i>in out</i>	String to fill
<i>Last</i>	<i>out</i>	Last index used in the string

## DESCRIPTION

This procedure receives one line from the remote host. A line consists into zero or more characters followed by an optional CR and by a LF. Those terminators are stripped before the line is returned.

This procedure blocks until one full line has been received.

## EXCEPTIONS

<b>Connection_Closed</b>	Peer has closed the connection before sending a whole line
--------------------------	--

SEE ALSO [Get (function)], page 9,  
 [Get\_Char (function)], page 9,  
 [Get\_Line (function)], page 10,  
 [Receive (procedure)], page 15,  
 [Set\_Buffer (procedure)], page 16.

**Get\_Receive\_Queue\_Size (function)**

PURPOSE Return the size of the unread data in the input queue

## PROTOTYPE

```

function Get_Receive_Queue_Size  [Sockets.Get_Receive_Queue_Size]
  (Socket : Socket_FD'Class)
  return Integer;

```

## PARAMETERS

<i>Socket</i>	<i>in</i>	Initialized and connected socket object
---------------	-----------	---

## RETURN VALUE

The non-negative size in bytes of the input queue

## DESCRIPTION

This function is only available on Linux platforms. On other operating systems, it will return -2 to indicate that the necessary mechanisms to retrieve the information are not available.

SEE ALSO [Receive (procedure)], page 15.

**Get\_Send\_Queue\_Size (function)**

PURPOSE Return the size of the unsent data in the output queue

## PROTOTYPE

```
function Get_Send_Queue_Size [Sockets.Get_Send_Queue_Size]
  (Socket : Socket_FD'Class)
  return Integer;
```

## PARAMETERS

*Socket*                    in            Initialized and connected socket object

## RETURN VALUE

The non-negative size in bytes of the output queue

## DESCRIPTION

This function is only available on Linux platforms. On other operating systems, it will return -2 to indicate that the necessary mechanisms to retrieve the information are not available.

SEE ALSO [Send (procedure)], page 16.

**Getsockopt (procedure)**

PURPOSE Retrieve a socket option

## PROTOTYPE

```
procedure Getsockopt (Socket : Socket_FD; [Sockets.Getsockopt]
  Level : Socket_Level := SOL_SOCKET;
  Optname : Socket_Option; Optval : out Integer);
```

## PARAMETERS

*Socket*                    in            Initialized and bound socket object  
*Level*                    in            Protocol level  
*Optname*                  in            Option name  
*Optval*                   out           Option value

## DESCRIPTION

This procedure retrieves options applicable to a socket. Please see your operating system manual for usable levels and options.

Two levels are defined: *SOL\_SOCKET* (the default) and *IPPROTO\_IP*. The options are *SO\_REUSEADDR*, *SO\_REUSEPORT*, *IP\_MULTICAST\_TTL*, *IP\_ADD\_MEMBERSHIP*, *IP\_DROP\_MEMBERSHIP*, *IP\_MULTICAST\_LOOP*, *SO\_SNDBUF* and *IP\_RCVBUF*.

Note that unlike their C language counterpart, *Getsockopt* and *Setsockopt* do not require an extra parameter representing the length in bytes of the option value. AdaSockets knows the right size for every option.

SEE ALSO [*Setsockopt* (procedure)], page 16.

**Listen (procedure)**

PURPOSE Establish a listen queue

## PROTOTYPE

```
procedure Listen (Socket : Socket_FD; [Sockets.Listen]
  Queue_Size : Positive := 5);
```

## PARAMETERS

*Socket*                    in            Initialized and bound socket object



*Queue\_Size*      in      Requested slots in the listen queue

#### DESCRIPTION

This procedure establishes a listen queue after a TCP socket as been initialized and bound. Each slot in the queue can hold one incoming connection that has not been accepted yet. Note that most operating systems ignore queue sizes larger than five.

SEE ALSO    [Accept\_Socket (procedure)], page 7,  
              [Bind (procedure)], page 8,  
              [Socket (procedure)], page 17.

### New\_Line (procedure)

PURPOSE    Send a CR/LF to a remote host

#### PROTOTYPE

```
procedure New_Line (Socket : Socket_FD'Class;      [Sockets.New_Line]
                   Count : Natural := 1);
```

#### PARAMETERS

*Socket*            in            Initialized and connected socket object  
*Count*            in            Number of CR/LF sequences to send

#### DESCRIPTION

This procedure sends one or more CR/LF combinations to the peer.

#### EXCEPTIONS

**Connection\_Closed**      Peer has prematurely closed the connection

SEE ALSO    [Put (procedure)], page 13,  
              [Put\_Line (procedure)], page 14.

### Put (procedure)

PURPOSE    Send a string to a remote host

#### PROTOTYPE

```
procedure Put (Socket : Socket_FD'Class;                      [Sockets.Put]
              Str : String);
```

#### PARAMETERS

*Socket*            in            Initialized and connected socket object  
*Str*                in            String to send

#### DESCRIPTION

This procedure sends the content of *Str* over an outgoing or incoming socket.

#### EXCEPTIONS

**Connection\_Closed**      Peer has prematurely closed the connection

SEE ALSO    [New\_Line (procedure)], page 13,  
              [Put\_Line (procedure)], page 14,  
              [Send (procedure)], page 16.

## Put\_Line (procedure)

PURPOSE Send a CR/LF terminated string to a remote host

PROTOTYPE

```
procedure Put_Line (Socket : Socket_FD'Class;      [Sockets.Put_Line]
                   Str : String);
```

PARAMETERS

<i>Socket</i>	in	Initialized and connected socket object
<i>Str</i>	in	String to send

DESCRIPTION

This procedure sends the content of *Str* plus a CR/LF combination over an outgoing or incoming socket.

EXCEPTIONS

<b>Connection_Closed</b>	Peer has prematurely closed the connection
--------------------------	--

SEE ALSO [New\_Line (procedure)], page 13,  
[Put (procedure)], page 13,  
[Send (procedure)], page 16.

## Receive (function)

PURPOSE Receive raw data over a socket

PROTOTYPE

```
function Receive (Socket : Socket_FD;              [Sockets.Receive]
                 Max : Ada.Streams.Stream_Element_Count := 4096)
                 return Ada.Streams.Stream_Element_Array;
```

PARAMETERS

<i>Socket</i>	in	Initialized and bound or connected socket object
<i>Max</i>	in	Maximum data length

RETURN VALUE

Received raw data

DESCRIPTION

This procedure receives data from a bound UDP socket or a connected TCP socket. Only one system call will be performed; this function will return whatever data has arrived. Note that in GNAT the secondary stack may be used to store the data and may result in stack storage exhaustion.

EXCEPTIONS

<b>Connection_Closed</b>	Peer has closed the connection before sending any data
--------------------------	--

SEE ALSO [Receive (procedure)], page 15,  
[Receive\_Some (procedure)], page 15,  
[Get\_Line (function)], page 10,  
[Get\_Line (procedure)], page 10.

## Receive (procedure)

PURPOSE Receive raw data over a socket

PROTOTYPE

```

procedure Receive (Socket : Socket_FD'Class;           [Sockets.Receive]
                   Data : out Ada.Streams.Stream_Element_Array);

```

PARAMETERS

<i>Socket</i>	in	Initialized and bound or connected socket object
<i>Data</i>	out	Incoming data buffer

DESCRIPTION

This procedure receives data from a bound UDP socket or a connected TCP socket. It will block until the *Data* reception buffer has been totally filled.

EXCEPTIONS

<b>Connection_Closed</b>	Peer has closed the connection before <i>Data</i> ' <b>Length</b> bytes were received
--------------------------	---

SEE ALSO [Get\_Line (function)], page 10,  
 [Get\_Line (procedure)], page 10,  
 [Receive (function)], page 14,  
 [Receive\_Some (procedure)], page 15.

## Receive\_Some (procedure)

PURPOSE Receive raw data over a socket

PROTOTYPE

```

procedure Receive_Some                               [Sockets.Receive_Some]
  (Socket : Socket_FD'Class;
   Data : out Ada.Streams.Stream_Element_Array;
   Last : out Ada.Streams.Stream_Element_Offset);

```

PARAMETERS

<i>Socket</i>	in	Initialized and bound or connected socket object
<i>Data</i>	out	Incoming data buffer
<i>Last</i>	out	Index of last element placed into <i>Data</i>

DESCRIPTION

This procedure receives data from a bound UDP socket or a connected TCP socket. As soon as at least one byte has been read, it returns with *Last* set to the index of the latest written element of *Data*.

EXCEPTIONS

<b>Connection_Closed</b>	Peer has closed the connection before sending any data
--------------------------	--

SEE ALSO [Get\_Line (function)], page 10,  
 [Get\_Line (procedure)], page 10,  
 [Receive (function)], page 14,  
 [Receive (procedure)], page 15.

## Send (procedure)

PURPOSE Send raw data over a socket

PROTOTYPE

```
procedure Send (Socket : Socket_FD;                                     [Sockets.Send]
                Data : out Ada.Streams.Stream_Element_Array);
```

PARAMETERS

<i>Socket</i>	in	Initialized and connected socket object
<i>Data</i>	out	Data to be sent

DESCRIPTION

This procedure sends data over a connected outgoing socket or over an incoming socket.

EXCEPTIONS

<b>Connection_Closed</b>	Peer has prematurely closed the connection
--------------------------	--

SEE ALSO [Put (procedure)], page 13,  
[Put\_Line (procedure)], page 14.

## Set\_Buffer (procedure)

PURPOSE Install a line-oriented buffer of the socket object

PROTOTYPE

```
procedure Set_Buffer                                     [Sockets.Set_Buffer]
  (Socket : Socket_FD'Class; Length : Positive := 1500);
```

PARAMETERS

<i>Socket</i>	in	Initialized and connected socket object
<i>Length</i>	in	Size in bytes of the newly installed buffer

DESCRIPTION

This procedure puts the socket object in buffered mode. If the socket was already buffered, the content of the previous buffer will be lost. The buffered mode only affects character- and line-oriented read operation such as [Get (function)], page 9, [Get\_Char (function)], page 9, and [Get\_Line (function)], page 10. Other reception subprograms will not function properly if buffered mode is used at the same time.

The size of the buffer has to be greater than the biggest possible packet sent by the remote host, otherwise data loss may occur.

SEE ALSO [Unset\_Buffer (procedure)], page 18.

## Setsockopt (procedure)

PURPOSE Set a socket option

## PROTOTYPE

```

procedure Setsockopt (Socket : Socket_FD;           [Sockets.Setsockopt]
                     Level : Socket_Level := SOL_SOCKET;
                     Optname : Socket_Option; Optval : Integer);

```

## PARAMETERS

<i>Socket</i>	in	Initialized and bound socket object
<i>Level</i>	in	Protocol level
<i>Optname</i>	in	Option name
<i>Optval</i>	in	Option value

## DESCRIPTION

This procedure sets options applicable to a socket. Please see your operating system manual for usable levels and options.

Two levels are defined: *SOL\_SOCKET* (the default) and *IPPROTO\_IP*. The options are *SO\_REUSEADDR*, *SO\_REUSEPORT*, *IP\_MULTICAST\_TTL*, *IP\_ADD\_MEMBERSHIP*, *IP\_DROP\_MEMBERSHIP*, *IP\_MULTICAST\_LOOP*, *SO\_SNDBUF* and *IP\_RCVBUF*.

Note that unlike their C language counterpart, *Getsockopt* and *Setsockopt* do not require an extra parameter representing the length in bytes of the option value. AdaSockets knows the right size for every option.

SEE ALSO [Getsockopt (procedure)], page 12.

**Shutdown (procedure)**

PURPOSE Shutdown a socket

## PROTOTYPE

```

procedure Shutdown                                     [Sockets.Shutdown]
    (Socket : in out Socket_FD; How : Shutdown_Type := Both);

```

## PARAMETERS

<i>Socket</i>	in out	Socket object to shutdown
<i>How</i>	in	Direction to shutdown

## DESCRIPTION

This procedure shutdowns either direction of the socket. *How* can take the value 'Send', 'Receive' or 'Both'.

SEE ALSO [Socket (procedure)], page 17.

**Socket (procedure)**

PURPOSE Create a socket of the given mode

## PROTOTYPE

```

procedure Socket (Socket : out Socket_FD;           [Sockets.Socket]
                  Domain : Socket_Domain := PF_INET;
                  Typ : Socket_Type := SOCK_STREAM);

```

## PARAMETERS

<i>Socket</i>	out	Socket object to initialize
<i>Domain</i>	in	Protocol family
<i>Typ</i>	in	Kind of sockets

## DESCRIPTION

This procedure initializes a new socket object by reserving a file descriptor to the operating system. For backward compatibility with older versions of this library, `AF_INET` is still accepted as a value but should be replaced as soon as possible with the proper `PF_INET`. Using `SOCK_STREAM` for the *Typ* argument will create a TCP socket while a `SOCK_DGRAM` will create a UDP one.

## EXAMPLE

```

declare
    Sock : Socket_FD;
begin
    -- Create a TCP socket
    Socket (Sock, PF_INET, SOCK_STREAM);
    -- Perform some operations on socket
    [...]
    -- Shutdown the socket in both directions
    Shutdown (Sock, Both);
end;
```

SEE ALSO [Shutdown (procedure)], page 17.

**Unset\_Buffer (procedure)**

PURPOSE Deinstall the line-oriented buffer of the socket object

## PROTOTYPE

```

procedure Unset_Buffer                                     [Sockets.Unset_Buffer]
    (Socket : Socket_FD'Class);
```

## PARAMETERS

*Socket*                      in              Initialized and connected socket object

## DESCRIPTION

This procedure deinstalls the buffer previously installed by [Set\_Buffer (procedure)], page 16. If any data is still present in the buffer, it will be lost. To avoid this situation, the buffer can be flushed by calling [Get (function)], page 9.

## 5 Sockets.Multicast package

The `Sockets.Multicast` allows the creation of IP multicast sockets.

```
type Multicast_Socket_FD is new           [Sockets.Multicast.Multicast_Socket_FD]
    Socket_FD with private;
```

The `Multicast_Socket_FD` tagged type derives from the `Socket_FD` type. It gets initialized by calling `[Create_Multicast_Socket (function)]`, page 20. An uninitialized `Multicast_Socket_FD` can be successfully compared to `Null_Multicast_Socket_FD`.

### Create\_Multicast\_Socket (function)

PURPOSE Create an IP multicast socket

PROTOTYPE

```
function                               [Sockets.Multicast.Create_Multicast_Socket]
    Create_Multicast_Socket (Group : String; Port : Natural;
    TTL : Positive := 16; Self_Loop : Boolean := True;
    Local_If : String := 0.0.0.0)
    return Multicast_Socket_FD;
```

PARAMETERS

<i>Group</i>	in	IP address of the multicast group to join
<i>Port</i>	in	Port of the multicast group to join
<i>TTL</i>	in	Time-to-live of sent packets
<i>Self_Loop</i>	in	Should the socket receive the packets sent from the local host?
<i>Local_If</i>	in	Address of the local interface to use

RETURN VALUE

The new initialized multicast socket

DESCRIPTION

This function creates an IP multicast socket attached to a given group, identified by its class E IP address and port.

Be careful when choosing the TTL parameter of your IP multicast socket. Most IP multicast routers do implement threshold-based filtering and will not let IP multicast packets leave your organization if the TTL on the last router is smaller than 16.

If 0 is given for the Port, a local one will be chosen. It can then later be retrieved using `Get_Sock_Port`.

EXAMPLE

```
declare
    Sock : Multicast_Socket_FD;
begin
    -- Create a multicast socket on group 224.1.2.3 port 8763
    Sock := Create_Multicast_Socket ("224.1.2.3", 8763);
    -- Perform some operations on socket
    [...]
    -- Shutdown the socket in both directions
```

```

        Shutdown (Sock, Both);
    end;

```

SEE ALSO [Send (procedure)], page 16,  
[Shutdown (procedure)], page 17.

## Create\_Multicast\_Socket (function)

PURPOSE Create an IP multicast socket

PROTOTYPE

```

function                                     [Sockets.Multicast.Create_Multicast_Socket]
    Create_Multicast_Socket (Group : String; Port : Positive;
    Local_Port : Natural; TTL : Positive := 16;
    Local_If : String := 0.0.0.0)
    return Multicast_Socket_FD;

```

PARAMETERS

<i>Group</i>	in	IP address of the multicast group to join
<i>Port</i>	in	Port of the multicast group to join
<i>Local_Port</i>	in	Local port number to use
<i>TTL</i>	in	Time-to-live of sent packets
<i>Local_If</i>	in	Address of the local interface to use

RETURN VALUE

The new initialized multicast socket

DESCRIPTION

This function creates an IP multicast socket attached to a given group, identified by its class E IP address and port. If *Local\_Port* is 0, a free port will automatically be chosen by your operating system.

This function should be used when you want to send packets to a multicast group without receiving any packet yourself.

EXAMPLE

```

declare
    Sock : Multicast_Socket_FD;
begin
    -- Create a multicast socket on group 224.1.2.3 port 8763
    Sock := Create_Multicast_Socket ("224.1.2.3", 8763);
    -- Perform some operations on socket
    [...]
    -- Shutdown the socket in both directions
    Shutdown (Sock, Both);
end;

```

SEE ALSO [Send (procedure)], page 16,  
[Shutdown (procedure)], page 17.



## 6 Sockets.Naming package

The `Sockets.Naming` package contains types and helper functions needed to manipulate Internet host names and addresses.

```
type Address is record                                     [Sockets.Naming.Address]
    H1, H2, H3, H4 : Address_Component;
end record;
```

This type represents an IPv4 address with H1 being the first octet and H4 the last one. For example, 137.194.161.2 is represented by H1=137, H2=194, H3=161, H4=2.

```
type Address_Array is array (Positive range               [Sockets.Naming.Address_Array]
    <>) of Address;
Helper type
```

```
type Address_Component is Natural range                  [Sockets.Naming.Address_Component]
    0 .. 255;
Helper type
```

```
type Host_Entry (N_Aliases, N_Addresses :                 [Sockets.Naming.Host_Entry]
    Natural) is new Ada.Finalization.Controlled with record
    Name : String_Access;
    Aliases : String_Array (1 .. N_Aliases);
    Addresses : Address_Array (1 .. N_Addresses);
end record;
```

The `Host_Entry` type holds a set of names and IP addresses associated with a host. Each host can have several IP address as well as several aliases.

```
type String_Access is access String;                     [Sockets.Naming.String_Access]
Helper type
```

```
type String_Array is array (Positive range <>) of        [Sockets.Naming.String_Array]
    String_Access;
Helper type
```

### Address\_Of (function)

PURPOSE Get the IP address of a host

PROTOTYPE

```
function Address_Of                                     [Sockets.Naming.Address_Of]
    (Something : String)
return Address;
```

PARAMETERS

*Something*            in            Host name or IP address

RETURN VALUE

IPv4 address

EXCEPTIONS

`Naming_Error`                    No information available for this name or address

SEE ALSO [Name\_Of (function)], page 24.

<i>Socket</i>	in	Connected socket object
---------------	----	-------------------------

## RETURN VALUE

Address of local interface used

SEE ALSO [Get\_Sock\_Port (function)], page 23,  
[Get\_Peer\_Addr (function)], page 22.

**Get\_Sock\_Port (function)**

PURPOSE Retrieve port used by local host

## PROTOTYPE

```
function Get_Sock_Port                                [Sockets.Naming.Get_Sock_Port]
    (Socket : Socket_FD)
    return Positive;
```

## PARAMETERS

Socket                      in                      Connected socket object

## RETURN VALUE

Port used on the local host

SEE ALSO [Get\_Peer\_Port (function)], page 22,  
[Get\_Sock\_Addr (function)], page 22.

**Host\_Name (function)**

PURPOSE Get the name of the current host

## PROTOTYPE

```
function Host_Name                                    [Sockets.Naming.Host_Name]
```

## RETURN VALUE

Name of the current host

## DESCRIPTION

This function returns the name of the current host. Depending on the local configuration, it may or may not be a fully qualified domain name (FQDN).

**Image (function)**

PURPOSE Make a string from an address

## PROTOTYPE

```
function Image (Add : Address)                        [Sockets.Naming.Image]
    return String;
```

## PARAMETERS

Add                      in                      IP address

## RETURN VALUE

String representation of the IP address

SEE ALSO [Value (function)], page 25.

**Info\_Of\_Name\_Or\_IP (function)**

PURPOSE Get addresses and names of a host

PROTOTYPE

```
function Info_Of_Name_Or_IP      [Sockets.Naming.Info_Of_Name_Or_IP]
    (Something : String)
    return Host_Entry;
```

PARAMETERS

*Something*            in            Host name or IP address

RETURN VALUE

Corresponding host entry

DESCRIPTION

This function extracts all the names and addresses from the naming service.

EXCEPTIONS

**Naming\_Error**                      No information available for this name or address

**Is\_IP\_Address (function)**

PURPOSE Check if given string is a valid IP address

PROTOTYPE

```
function Is_IP_Address           [Sockets.Naming.Is_IP_Address]
    (Something : String)
    return Boolean;
```

PARAMETERS

*Something*            in            String to check

RETURN VALUE

'True' if *Something* is an IP address

**Name\_Of (function)**

PURPOSE Official name of the host

PROTOTYPE

```
function Name_Of (Something : String)      [Sockets.Naming.Name_Of]
    return String;
```

PARAMETERS

*Something*            in            Host name or IP address

RETURN VALUE

Name of the host

EXCEPTIONS

**Naming\_Error**                      No information available for this name or address

SEE ALSO [Address\_Of (function)], page 21.

**Value (function)**

PURPOSE Transform a string into an address

PROTOTYPE

```
function Value (Add : String)                                [Sockets.Naming.Value]  
    return Address;
```

PARAMETERS

*Add* in Textual representation of an IP address

RETURN VALUE

Corresponding Address

SEE ALSO [Image (function)], page 23.



## Appendix A Contributors

AdaSockets has been originally developped by Samuel Tardieu who still maintains it. However, the following people have made crucial contributions to AdaSockets, be they new code, bug fixes or porting to new operating systems:

- Dmitriy Anisimkov ([anisimkov@yahoo.com](mailto:anisimkov@yahoo.com))
- Alan Barnes ([barnesa@aston.ac.uk](mailto:barnesa@aston.ac.uk))
- Juanma Barranquero ([lektu@terra.es](mailto:lektu@terra.es))
- Bobby D. Bryant ([bdbryant@mail.utexas.edu](mailto:bdbryant@mail.utexas.edu))
- Sander Cox ([sander.cox@philips.com](mailto:sander.cox@philips.com))
- Sune Falk ([sune.falck@telia.com](mailto:sune.falck@telia.com))
- Guillaume Foliard ([guifo@wanadoo.fr](mailto:guifo@wanadoo.fr))
- Laurent Guerby ([guerby@club-internet.fr](mailto:guerby@club-internet.fr))
- David J. Kristola ([David95037@aol.com](mailto:David95037@aol.com))
- Dominik Madon ([dominik@acm.org](mailto:dominik@acm.org))
- Pascal Obry ([p.obry@wanadoo.fr](mailto:p.obry@wanadoo.fr))
- Nicolas Ollinger ([Nicolas.Ollinger@ens-lyon.fr](mailto:Nicolas.Ollinger@ens-lyon.fr))
- Stphane Patureau ([spaturea@meletu.univ-valenciennes.fr](mailto:spaturea@meletu.univ-valenciennes.fr))
- Thomas Quinot ([thomas@cuivre.fr.eu.org](mailto:thomas@cuivre.fr.eu.org))
- Preben Randhol ([randhol@pvv.org](mailto:randhol@pvv.org))
- Maxim Reznik ([max1@mbank.com.ua](mailto:max1@mbank.com.ua))
- Joel Sherrill ([joel.sherrill@oarcorp.com](mailto:joel.sherrill@oarcorp.com))
- Samuel Tardieu ([sam@rfc1149.net](mailto:sam@rfc1149.net))

If you feel that you have been forgotten, please send me a mail so that I can fix it in the next version.

See Appendix B [Resources on the Internet], page 29, for how to contribute.





## Appendix B Resources on the Internet

The latest version of AdaSockets can always be found at:

<http://www.rfc1149.net/devel/adasockets>

You can report issues or submit questions on GitHub's issue tracker at:

<https://github.com/samueltardieu/adasockets/issues>



# Index

## A

Accept\_Socket ..... 7  
 Accepting a new connection ..... 7  
 Ada.Streams.Stream\_Element\_Array .. 6, 14, 15, 16  
 Ada.Streams.Stream\_Element\_Count ..... 14, 15  
 AdaSockets presentation ..... 1  
 Address ..... 21  
 Address\_Array ..... 21  
 Address\_Component ..... 21  
 Address\_Of ..... 21  
 AF\_INET ..... 18  
 Any\_Address ..... 22  
 Assigning a local port ..... 8

## B

Bind ..... 8  
 Binding a socket ..... 8  
 Both ..... 17

## C

Closing a socket ..... 17  
 Comparison with GNAT.Sockets ..... 1  
 Connect ..... 8  
 Connecting a socket ..... 8  
 Connection\_Closed ..... 9, 10, 11, 13, 14, 15, 16  
 Connection\_Refused ..... 8  
 Contributing ..... 27, 29  
 Create\_Multicast\_Socket ..... 5, 19, 20  
 Creating a multicast socket ..... 5, 19, 20  
 Creating a server ..... 8  
 Creating a socket ..... 5, 17, 19, 20  
 Creating a TCP socket ..... 5  
 Creating a UDP socket ..... 5  
 Creating a unicast socket ..... 5  
 CR ..... 10, 11, 13

## E

Establishing a listen queue ..... 12

## F

Finding AdaSockets on the Internet ..... 29

## G

Get ..... 9  
 Get\_Char ..... 9  
 Get\_Line ..... 10, 11  
 Get\_Peer\_Addr ..... 22  
 Get\_Peer\_Port ..... 22  
 Get\_Receive\_Queue\_Size ..... 11  
 Get\_Send\_Queue\_Size ..... 12  
 Get\_Sock\_Addr ..... 22  
 Get\_Sock\_Port ..... 23  
 Getsockopt ..... 12  
 Group communication ..... 5

## H

Handling a new connection ..... 7  
 Host\_Entry ..... 21  
 Host\_Name ..... 23

## I

Image ..... 23  
 Info\_Of\_Name\_Or\_IP ..... 24  
 Installing AdaSockets ..... 3  
 IP\_ADD\_MEMBERSHIP ..... 12, 17  
 IP\_DROP\_MEMBERSHIP ..... 12, 17  
 IP\_MULTICAST\_LOOP ..... 12, 17  
 IP\_MULTICAST\_TTL ..... 12, 17  
 IPPROTO\_IP ..... 12, 17  
 Is\_IP\_Address ..... 24

## L

LF ..... 10, 11, 13  
 Listen ..... 12  
 Listen queue ..... 12

## M

Manipulating socket options ..... 12, 16  
 Mbone ..... 5  
 Multicast sockets ..... 5  
 Multicast\_Socket\_FD ..... 5, 19

## N

Name\_Of ..... 24  
 Naming\_Error ..... 21, 24  
 New\_Line ..... 13

**P**

PF_INET .....	18
Put .....	13
Put_Line .....	14

**R**

Raw data manipulation .....	6
Receive .....	14, 15, 17
Receive_Some .....	15
Receiving data .....	6, 9, 10, 11, 14, 15, 16, 18
Reporting a bug .....	29
Representing IP addresses .....	23, 25
Retrieving socket options .....	12

**S**

Send .....	16, 17
Sending data .....	6, 11, 13, 14, 16
Sending patches .....	29
Set_Buffer .....	16
Setsockopt .....	17
Setting socket options .....	16
Shutdown .....	17
SO_RCVBUF .....	12, 17
SO_REUSEADDR .....	12, 17
SO_REUSEPORT .....	12, 17
SO_SNDBUF .....	12, 17
SOCK_DGRAM .....	18
SOCK_STREAM .....	18
Socket .....	5, 17
Socket shutdown .....	17
Socket_Error .....	8
Socket_FD .....	5, 7
Sockets.Accept_Socket .....	7
Sockets.Bind .....	8
Sockets.Connect .....	8
Sockets.Get .....	9
Sockets.Get_Char .....	9
Sockets.Get_Line .....	10, 11
Sockets.Get_Receive_Queue_Size .....	11
Sockets.Get_Send_Queue_Size .....	12
Sockets.Getsockopt .....	12
Sockets.IP_ADD_MEMBERSHIP .....	12, 17
Sockets.IP_DROP_MEMBERSHIP .....	12, 17
Sockets.IP_MULTICAST_LOOP .....	12, 17
Sockets.IP_MULTICAST_TTL .....	12, 17
Sockets.IPPROTO_IP .....	12, 17
Sockets.Listen .....	12

Sockets.Multicast.Create_	
Multicast_Socket .....	5, 19, 20
Sockets.Naming.Address_Of .....	21
Sockets.Naming.Any_Address .....	22
Sockets.Naming.Get_Peer_Addr .....	22
Sockets.Naming.Get_Peer_Port .....	22
Sockets.Naming.Get_Sock_Addr .....	22
Sockets.Naming.Get_Sock_Port .....	23
Sockets.Naming.Host_Name .....	23
Sockets.Naming.Image .....	23
Sockets.Naming.Info_Of_Name_Or_IP .....	24
Sockets.Naming.Is_IP_Address .....	24
Sockets.Naming.Name_Of .....	24
Sockets.Naming.Value .....	25
Sockets.New_Line .....	13
Sockets.Put .....	13
Sockets.Put_Line .....	14
Sockets.Receive .....	14, 15
Sockets.Receive_Some .....	15
Sockets.Send .....	16
Sockets.Set_Buffer .....	16
Sockets.Setsockopt .....	17
Sockets.Shutdown .....	17
Sockets.SO_RCVBUF .....	12, 17
Sockets.SO_REUSEADDR .....	12, 17
Sockets.SO_REUSEPORT .....	12, 17
Sockets.SO_SNDBUF .....	12, 17
Sockets.Socket .....	5, 17
Sockets.SOL_SOCKET .....	12, 17
Sockets.Unset_Buffer .....	18
SOL_SOCKET .....	12, 17
Stream_Element_Array .....	6, 14, 15, 16
Stream_Element_Count .....	14, 15
String_Access .....	21
String_Array .....	21
Suggesting a feature .....	29

**T**

TCP socket .....	5
------------------	---

**U**

UDP socket .....	5
Unicast sockets .....	5
Unset_Buffer .....	18

**V**

Value .....	25
-------------	----